

# INDUSTRIAL FIELD REPORT

## SEWAGE WATER CLEANING - TANKS



### 1 SITUATION

CP Kelco is a global producer of hydrocolloids. At the facility in Denmark they needed the floor of 2 sewage water tanks on 450 m2 each to be recoated.

The facility could not live with a long shutdown time because of a 50 % reduction of production in the factory.

### 2 SOLUTION

LINE-X® XS-350 was sprayed 3.18 mm ( 1/8 inch ) thick onto primed concrete creating a monolithic, impervious protective lining with tenacious adhesion. The difference in thickness was less than 4 % calculated over all 900 m2 thanks to our skilled applicators.

### 3 AFTER APPLICATION

Each tank was completed in one week and back in service 12 hours after application.

#### INDUSTRIAL CUSTOMER

CP Kelco A/S  
[www.cpkelco.com](http://www.cpkelco.com)

#### LOCATION

CP Kelco A/S  
Ved Banen 16  
DK- 4623 Lille Skensved  
Denmark

#### APPLICATOR

LINE-X Protective Coatings  
Denmark A/S  
(+45) 39 30 33 88 |  
[kasper@line-x.dk](mailto:kasper@line-x.dk)

#### FORMULATION

Concrete moisture cured sealer/primer. LINE-X XS350  
100% solids polyurea  
sprayed on lining

#### APPLICATION SYSTEM

GRACO FOAMCAT 200  
with Fusion Gun

For more information on LINE-X Industrial Coatings Division, please contact:

6 Hutton Centre Drive, Suite 500, Santa Ana, California USA 92707 | (800) 831-3232 (Office) | [www.line-xicd.com](http://www.line-xicd.com)

